

AMSOIL Material Safety Data Sheet

Date Issued/Revised: December 12, 2008
Supersedes:


Section 1: Product and Company Identification

Manufacturer: AMSOIL, Inc.
925 Tower Avenue
Superior, WI 54880

Telephone: CHEMTREC (Spill Emergency Only): 1-800-424-9300
Information: 715-392-7101

AMSOIL Product Code DRC
Product Label Name AMSOIL DIESEL RECOVERY
Product Use DIESEL FUEL TREATMENT

NFPA Rating



Section 2: Composition/Information on Ingredients

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

COMPONENT	CAS NUMBER	% by Wt.
Stoddard Solvent	8052-41-3	75 - 85
Petroleum Naphtha	64742-94-5	5 - 15
Tetramethylbenzene	527-53-7	2 - 5
Naphthalene	91-20-3	< 1

Section 3: Hazards Identification

POTENTIAL HEALTH EFFECTS:

WARNING:

- Harmful or fatal if swallowed
- Combustible

EYE: May cause mild eye irritation. Symptoms include stinging, tearing and redness.

SKIN: Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of the skin, burns and other skin damage. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during normal use.

INHALATION: Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms include irritation of the nose, throat and airways. Extended exposure may lead to central nervous system depression, including dizziness, drowsiness, weakness, fatigue, nausea, headache and unconsciousness.

INGESTION: Ingestion may cause gastrointestinal disturbance, including irritation, nausea, vomiting and diarrhea. The major health threat of ingestions occurs from the danger of aspiration of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia, severe lung damage and even death.

CHRONIC EFFECTS: Prolonged or repeated exposure to vapors may lead to central nervous system effects.

TARGET ORGANS: Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the mail rat and the kidney effects are not expected to occur in humans.

Section 4: First Aid Measures

- Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
- Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Wash contaminated clothing prior to re-use.
- Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
- Ingestion:** Do NOT induce vomiting. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Monitor for breathing difficulties. Mouth can be rinsed to dissipate the taste.
- Note to Physicians:** Treat symptomatically. Pre-existing skin or lung conditions may be aggravated by exposure.

Section 5: Fire Fighting Measures

- Flammable Properties:** In accordance with OSHA definitions, this product is a Class II combustible liquid.
- | | | | |
|---------------------------|-------------|------------------------|-----|
| Flash Point: | 107 F (TCC) | Upper Explosive Limit: | 6.0 |
| Autoignition Temperature: | 500 F | Lower Explosive Limit: | 1.0 |
- Suitable Extinguishing Media:** Use extinguishers rated for Class B fires, such as dry chemical, Halon, fire fighting foam or CO2.
- Products of Combustion:** Oxides of carbon
- Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

- Personal Precautions:** Use personal protection recommended in Section 8.
- Environmental Precautions:** Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.
- Methods for Containment & Clean-up:** Remove all sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

- Handling Procedures:** Keep away from heat, sparks and open flame. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion. Provide adequate ventilation during use. Do not breathe vapors. Wash hands after use.

AMSOIL Material Safety Data Sheet

Date Issued/Revised: December 12, 2008
Supersedes:

Storage Procedures: Store in a cool dry area out of direct sunlight. Store in a well ventilated area. Keep out of reach of children.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Stoddard Solvent	500	NE	100	NE	NE		ppm
Petroleum Naphtha	NE	NE	NE	NE	NE		
Tetramethylbenzene	NE	NE	NE	NE	NE		
Naphthalene	10	15(v)	10 (s)	15	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use NIOSH-approved self-contained positive pressure respirators in low circulation areas and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, neoprene or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State Liquid
 Initial Boiling Point..... >300°F
 Vapor Pressure ~ 0.06 mmHg @ 68°F
 Vapor Density (Air=1).....>4
 Evaporation Rate (ether=1).....<1
 Solubility in Water Insoluble
 Specific Gravity (Water=1) 0.8610
 pH.....Not Determined
 Odor Petroleum
 Appearance..... Light Amber
 Volatile Organic Compounds: wt %: 94.22 g/L: 740.5 lbs./gal: 6.17
 Viscosity IndexNot Applicable

AMSOIL Material Safety Data Sheet

Date Issued/Revised: December 12, 2008
Supersedes:

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: temperature extremes, sources of ignition

Incompatible Materials: Strong oxidizers

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, various hydrocarbons

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Petroleum Naphtha	LD50	7050 mg/kg	Oral	Rat
Petroleum Naphtha	LC50	590 mg/m ³ /4H	Inhalation	Rat
Naphthalene	LD50	490 mg/kg	Oral	Rat
Naphthalene	LD50	> 20 g/kg	Dermal	Rabbit

CHRONIC EFFECTS

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	Naphthalene	Hazard Communication Carcinogen
IARC:	Naphthalene	2B – Possibly Carcinogenic
NTP:	Naphthalene	Reasonably Anticipated to be a Carcinogen

Mutagenicity: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	Naphthalene -- 48 Hr EC50 water flea: 2.16 mg/L
Persistence / Degradability:	No information available
Bioaccumulation / Accumulation:	No information available
Mobility in Environment:	No information available

Section 13: Disposal Considerations

Disposal: This product is a RCRA hazardous waste for the toxicity characteristic: D018 (9.6 mg/L Benzene).
(See 40 CFR Part 261.20 – 261.33)

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

AMSOIL Material Safety Data Sheet

Date Issued/Revised: December 12, 2008
Supersedes:

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Not Regulated

Special Provisions: This product is reclassified as combustible, but no markings or placarding are required per 49 CFR 173.150(f)(2).

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Naphthalene (100 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	Yes
	Chronic Health Hazard	Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
Naphthalene (0.95%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Naphthalene

Consumer Product Safety Act General Conformity Certification: This product was evaluated by CRC Industries, Inc., and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location listed in Section 1 of this MSDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

Naphthalene (0.95%),
Benzene (0.001%)

State Right to Know:

New Jersey: 91-20-3, 8052-41-3
Pennsylvania: 91-20-3, 95-63-6, 8052-41-3

AMSOIL Material Safety Data Sheet

Date Issued/Revised: December 12, 2008
Supersedes:

Massachusetts: 91-20-3, 8052-41-3
Rhode Island : 91-20-3, 8052-41-3

Additional Regulatory Information: This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

I

Section 16: Other Information

The information and recommendations contained herein are, to the best of AMSOIL's knowledge and belief, accurate and reliable as of the date issued. AMSOIL makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and AMSOIL shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with AMSOIL's interpretation of the available data.